



PRODUCT INFORMATION

Evaporator Model	CTD20/632H-HCC			
Type	Direct Expansion (DX)			
Refrigerant	R404A			
Selection condition	SC1	SC2	SC3	SC4
	(Te = 0°C, RT= 10°C)	(Te = - 8 °C, RT= 0°C)	(Te = - 25 °C, RT= -18°C)	(Te = - 31 °C, RT= -25°C)
Cooling Capacity	45.86kW	30.17kW	20.75kW	15.43kW
Surface Area	118.7m ²			

TECHNICAL DETAILS

Fin Material	Aluminium
Fin Spacing	7 mm
Tube Material	Copper
Tube Volume	32.12 L
Casing	G.I Powder coated


FAN & AIR FLOW

No. of fans	2
Fan Diameter	630 mm
Speed per fan	1320 rpm
Electric Power / fan	800 W
Air Flow	20000 m ³ /h
Air Throw	19 m


DEFROSTING

Defrosting type	Electric
Coil Heater	12500W
Tray Heater	2400W

DIMENSIONS



All Dimensions are in mm.



NOTE:

- ❖ The actual air throw varies with product loading and several other factors.
- ❖ It is advised that the unit should not be used in a corrosive atmosphere.
- ❖ All data are subjected to change without prior notice.
- ❖ The fan and heater data could change slightly depending on the manufacturer's design and data changes.
- ❖ The technical and commercial information provided in this data sheet is a property of ColdTech Group, UAE
info@coldtechgroup.com