



## PRODUCT INFORMATION

Evaporator Model	:	CTL30/503-HCC	
Type	:	Direct Expansion (DX)	
Refrigerant	:	R404A	
Selection condition	:	SC1	SC2
		(Te = 0°C, RT= 10°C)	(Te = - 8 °C, RT= 0°C)
Cooling Capacity	:	41.21kW	27.48kW
Surface Area	:	133.75m <sup>2</sup>	

## TECHNICAL DETAILS

Fin Material	:	Aluminium
Fin Spacing	:	4.5 mm
Tube Material	:	Copper
Tube Volume	:	27.4 L
Casing	:	G.I Powder coated


## FAN & AIR FLOW

No. of fans	:	3
Fan Diameter	:	500 mm
Speed per fan	:	1300 rpm
Electric Power / fan	:	414 W
Air Flow	:	14000 m <sup>3</sup> /h
Air Throw	:	16 m

## DEFROSTING

Defrosting type	:	Electric
Coil Heater	:	6000W
Tray Heater	:	NA

## DIMENSIONS



### NOTE:

- ❖ The actual air throw varies with product loading and several other factors.
- ❖ It is advised that the unit should not be used in a corrosive atmosphere.
- ❖ All data are subjected to change without prior notice.
- ❖ The fan and heater data could change slightly depending on the manufacturer's design and data changes.
- ❖ The technical and commercial information provided in this data sheet is a property of ColdTech Group, UAE  
info@coldtechgroup.com